

If not otherwise specified:
Dist/Dim in meters
Weights in m.tones

All details given in good faith without any guarantee

Builders	
Classification	DNV GL / 100 A5 E Multi-purpose dry cargo ship Equipped for carriage of containers DBC SOLAS-II-2,Reg.19 G Strengthened for heavy cargo MC E AUT
Length oa	88.3
Breadth mld	12.4
Depth mld	7.76
Draft summer	5.14
Deadweight summer draft	3595
Draft winter	5.04
Deadweight winter draft	3484
Gross tonnage	2451
Net tonnage	1325
Immersion(load draft) TPC	10.55
Mean draft of ship in heavy ballast	3.1
Distance from forward end of No. 1 hatch to aft end of last hatch	58.5
Hatch type	System TTS multifold crocodile
Container (TEU) capacity Hold / Deck	0 / 20

Hatch details:

- a : Distance from waterline fully ballasted to top of hatch coamings
- b : Distance from waterline fully loaded to top of hatch coamings
- c : Distance from tank top to top of hatch coamings
- d : Max permissible loading on hatch covers
- e : Distance from ship's rail to inside hatch coamings
- f : Height of hatch coamings
- g : Hatch opening
- h : No. of Loadingholes on hatchcovers X diameter in mm

Remarks:

- 2 movable bulkheads/9 different positions/4 different compartments.
- Equipped for carriage of containers only on hatch 2 (20 TEU).
- Equipped for dangerous goods.
- Hatch opening (g) is excl. Bulkheads.
- Hold dimensions are incl. Bulkheads in parked positions.
- Thickness of bulkheads are 275mm each.
- A60

Htch#	a	b	c	d	e	f	g	h
1	5.85	3.9	7.95	1.6	1.1	2.25	25.2 x 10.1	6 x 600
2	5.85	3.9	7.95	1.6	1.1	2.25	31.8 x 10.1	8 x 600

Hold#	Bale		Grain		Hold dimensions
	cbm	cbft	cbm	cbft	
1	1938	68451	1950	68864	24.7 x 10.1 x 7.77
2	2461	86919	2477	87474	31.3 x 10.1 x 7.77

Compartments	a	b	c	d	e	f	g	h	i	j	k	l	m
	321	120	239	334	500	168	179	317	215	689	784	168	226
	168	226	0	0	0	0	0	0	0	0	0	0	0

Ex. 9313747
IMO No 8PBH4
Call sign 2010
Build BRB
Flag

Max permissible load on deck/hatch-cover, mt/sqm	1.6
Max permissible load on tanktop, mt/sqm	15
Max air draft - 1	19.25
Max air draft - 2	0
Water ballast capacity	1377
MGO Capacity (Cbm)	44
Service speed, knots	10
A60	Yes
Bow thruster	130 kW, Yes
Boxed	Yes
Open hatch	Yes
Rhine fitted	No
Ammonium Nitrate fitted	Yes
FeSi fitted	Yes
Keel to top antenna fwd/aft	21 / 23.7
Keel to top antenna fwd/aft - lowered mast	13.5 / 17.5

Communication	
Email	Wilson Avonmouth <w.avonmouth@wilsonfleet.no>
Phone	47 190853984 Mobile
SatPhone	47 121569876 V-SAT