

FORW. CARGO BHD

If not otherwise specified:
Dist/Dim in meters
Weights in m.tones

All details given in good faith without any guarantee

Builders	
Classification	DNV GL / 100 A5 E G AHTS SOLAS-II-2, Reg.19 DBC MC E AUT
Length oa	87.83
Breadth mld	12.8
Depth mld	7.1
Draft summer	5.606
Deadweight summer draft	3760
Draft winter	5.491
Deadweight winter draft	3642
Gross tonnage	2452
Net tonnage	1369
Immersion(load draft) TPC	10.1
Mean draft of ship in heavy ballast	3.25
Distance from forward end of No. 1 hatch to aft end of last hatch	57.2
Hatch type	Kvaerner Multifold crocodile, with hydraulic control
Container (TEU) capacity Hold / Deck	0 / 36

Hatch details:

a : Distance from waterline fully ballasted to top of hatch coamings
b : Distance from waterline fully loaded to top of hatch coamings
c : Distance from tank top to top of hatch coamings
d : Max permissible loading on hatch covers
e : Distance from ship's rail to inside hatch coamings
f : Height of hatch coamings
g : Hatch opening
h : No. of Loadingholes on hatchcovers X diameter in mm

Remarks:

* Height in hold: 7.99 m under hatch hinges.
Hold length is 55.84 with bulkheads in storage pos.

2 moveable bulkheads with 10 positions and 2 storage positions.
Cubic capacity without bulkheads is 4672 cbm.
FESI fitted for packaged goods only.

A-60: Located adjacent to engine room bulkhead insulated to A-60 standard
NAABSA : Check C/P

Htch#	a	b	c	d	e	f	g	h
1	6.1	3.85	8.2	1.6	1.3	2.4	56.55 x 10.2	4 x 670

	Bale		Grain		
Hold#	cbm	cbft	cbm	cbft	Hold dimensions
1	4588	162024	4588	162024	56.55 x 10.2 x 8.13

Compartments	a	b	c	d	e	f	g	h	i	j	k
	396	450	260	471	496	525	335	632	276	381	451

Ex. Theseus
IMO No 9390159
Call sign 8PBL2
Build 2009
Flag BRB

Max permissible load on deck/hatch-cover, mt/sqm	1.6
Max permissible load on tanktop, mt/sqm	15
Max air draft - 1	22
Max air draft - 2	15.7
Water ballast capacity	1340
MGO Capacity (Cbm)	175
IFO Capacity (Cbm)	90
Service speed, knots	9
A60	Yes
Bow thruster	185 kW, Yes
Boxed	Yes
Open hatch	Yes
Rhine fitted	No
Ammonium Nitrate fitted	Yes
FeSi fitted	No
Keel to top antenna fwd/aft	20.3 / 25.3
Keel to top antenna fwd/aft - lowered mast	11.5 / 19

Communication	
Email	Wilson Dundee <w-dundee@com4sea.de>
Phone	49 151 550 179 07 Mobile
SatPhone	49 5932 500 94 01 V-Sat